



Cooler Cleaning Instructions

Before you Begin: Identify Your Cooler. Have a look at the manufacturer's sticker on the rear of your cooler to determine which series cooler you have. For E & S Series, go to A. For R, P and G Series, go to B.

A: Crystal Mountain E & S Series Cleaning Instructions:

- 1) Unplug and approach the cooler from the front.
- 2) Remove the bottle and drain any water in the reservoir through the faucets.
- 3) Remove the locking pin from the Crystal Cone, which may be stiff, requiring a tool. Use the fingertips of both hands to press on the Cone and turn counter-clockwise until it is free from the cooler opening.
- 4) Using fingers of both hands, loosen and remove the insulation jacket covering the plastic reservoir from the cooler opening by lifting it straight up through the opening.
- 5) Remove the baffle cup by lifting straight out. Loosen & remove the baffle stem and wing nut by turning counterclockwise.
- 6) Remove tops of faucets by turning them counter clockwise.
- 7) Remove the faucets from the reservoir elbows by turning them counter clockwise.
- 8) Approach the cooler from the rear and open and unhook the latch provided on the evaporator band.
- 9) Using both hands, loosen the reservoir from the evaporator band and lift it straight through the cooler opening.
- 10) Sanitize the reservoir, baffle, and faucet in the dishwasher, or with the cooler cleaning kits available at SASI Spring Water.
- 11) To reinstall, reverse this procedure. (If you have any problems contact us for assistance)

B: Crystal Mountain R, P & G Series Cleaning Instructions:

- 1) Unplug and approach the cooler from the front.
- 2) Remove the bottle and drain any water in the reservoir through the faucets.
- 3) Remove the locking pin from the Crystal Cone by pressing with the fingertips of both hands and turning it counter clockwise until it is free from the cooler opening.
- 4) Using the fingers of both hands, loosen and remove the insulation jacket covering the plastic reservoir from the cooler opening.
- 5) Remove tops of faucets by turning them counter clockwise.
- 6) Remove the faucets from the reservoir elbows by turning them counter clockwise.
- 7) Approach the cooler from the rear and open and unhook the latch provided on the evaporator band.
- 8) Using both hands, loosen the reservoir from the evaporator band and lift it straight through the cooler opening.
- 9) Sanitize the reservoir, baffle, and faucet in the dishwasher, or with the cooler cleaning kits available at SASI Spring Water.
- 10) To reinstall, reverse this procedure. (If you have any problems contact us for assistance)



Cooler Cleaning Instructions

